



DRAFT

**State of West Virginia
Department of Environmental Protection
Division of Water and Waste Management
601 57th Street, SE
Charleston, WV 25304-2345
General
National Pollution Discharge Elimination System
Water Pollution Control Permit**

Permit No.: WV0116025

Issue Date:

**Subject: Stormwater Discharges
From small Municipal Separate
Storm Sewer Systems**

Effective Date:

Expiration Date:

**Supersedes: WV/NPDES General
Water Pollution Control Permit No.
WV0116025, issued July 22, 2009**

To Whom It May Concern:

This is to certify that owners and operators of small municipal separate storm sewer systems (MS4s) located in the State of West Virginia who have satisfied the registration requirements and who have agreed to be regulated under the terms and conditions of this general permit are hereby granted coverage under this General WV/NPDES Water Pollution Control Permit to discharge stormwater into waters of the State.

All operators of regulated small municipal separate storm sewer systems are required to apply for and obtain coverage in accordance with this permit, unless waived in accordance with CFR §122.32(a).

This permit is subject to the following terms and conditions:

The information submitted on and with the site registration application form, once approved, will hereby be known as the stormwater management program (SWMP). The SWMP once approved, will be made terms and conditions of the permit with like effect as if all such information were set forth herein, and other conditions set forth in Parts I, II, III, IV, Appendices A through D and the SWMP approval letter.

Table of Contents

Part I.....	4
A. Coverage under Permit WV0116025.....	4
1. Permit Area.....	4
2. Eligibility.....	4
3. Limitations on Coverage.....	4
4. Continuation of this General Permit.....	6
5. Maximum Extent Practicable (MEP).....	6
Part II.....	7
A. Notice of Intent (NOI) and SWMP Applications.....	7
1. Deadline for Notification.....	7
2. Deadline for SWMP.....	7
3. Co-permittees Under a Single NOI.....	7
4. Where to Submit.....	7
B. Requirements of SWMP.....	7
1. Existing Permittees.....	7
2. New Permittees.....	7
3. Public Notice.....	7
4. Minimum Control Measures.....	8
5. Extension of Milestones.....	8
6. Implementation and Enforcement.....	8
7. Evaluation.....	8
8. BMPs for Discharges to 303d and TMDL Receiving Waters.....	8
9. Wasteload Allocations.....	8
10. Annual Report.....	8
C. Stormwater Management Program for Small MS4s.....	9
1. Best Management Practices.....	9
2. Implementation.....	9
3. Coordination Among Permittees.....	9
4. Relying on Others.....	9
5. Roles and Responsibilities.....	9
6. Discharges to Common Water Bodies.....	9
7. Minimum Control Measures.....	9
a) Public Education and Outreach.....	9
b) Public Involvement and Participation.....	11
c) Illicit Discharge Detection and Elimination (IDDE).....	11
d) Controlling Runoff from Construction Sites.....	16
Part III. Special Conditions.....	33
A. Sharing Responsibility.....	33
B. Compliance of Discharge with Water Quality Standards.....	33
C. Requiring an Individual Permit.....	33
D. Discharge to Impaired Waters.....	33

DRAFT

2. Discharging into Waters with Approved TMDLs	34
E. Endangered and Threatened Species	34
Part IV	35
A. Monitoring, Recordkeeping, Evaluation, Reporting and Program Review.....	35
1. Stormwater Monitoring	35
2. Recordkeeping and Public Availability of SWMP and Annual Report.....	36
3. Program Evaluation	37
4. Annual Report	37
5. Program Review	38
Appendix A	39
Appendix B.....	40
Appendix C.....	44
Appendix D	48

DRAFT

Part 1

DRAFT

A. Coverage under Permit WV0116025

1. Permit Area

This permit authorizes discharges composed of stormwater from regulated Small Municipal Separate Storm Sewer Systems (SMS4) in all areas of the State of West Virginia.

2. Eligibility

- a) Eligible jurisdictions include but are not limited to municipalities, counties, transportation facilities, and federal and state owned facilities that are located within the boundaries of a Bureau of the Census defined “Urbanized Area” (UA) based on the latest decennial census,
- b) Jurisdictions that are located fully or partially within an urbanized area as determined by the latest Decennial Census by the Bureau of Census are eligible for coverage.
- c) Areas may be designated for permit authorization by the Department of Environmental Protection (Department) or the Environmental Protection Agency (EPA) pursuant to (40 CFR) 122.26, 122.32, and 40 CFR 123.35.
- d) The Department may designate municipalities under 40 CFR 122.32(a)(2) by using the following criteria to evaluate and determine if the subject MS4 requires permit coverage:
 - 1) Population greater than 1000,
 - 2) High population density,
 - 3) Contiguity to an urbanized area,
 - 4) High growth or growth potential,
 - 5) Discharge to sensitive waters,
 - 6) Significant contributor of pollutants to waters of the State,
 - 7) Ineffective protection of water quality by other programs
- e) Permit coverage may be granted to jurisdictions owning or operating a small MS4 within the permit area, provided a Notice of Intent in accordance with Part II of this permit is submitted to the Department.

3. Limitations on Coverage

- a) This permit authorizes the following non-stormwater discharges provided they have been determined not to be substantial contributors of pollutants to a particular small MS4 applying for coverage under this permit.

- 1) Uncontaminated water line flushing unless documented health or safety emergencies occur,
- 2) Landscape irrigation,
- 3) Diverted stream flows,
- 4) Uncontaminated ground water infiltration (as defined at 40 CFR 35.2005(20)),
- 5) Uncontaminated pumped groundwater,
- 6) Discharges from potable water sources,
- 7) Foundation drains,
- 8) Air conditioning condensate,
- 9) Irrigation water,
- 10) Springs,
- 11) Water from crawl space pumps,
- 12) Footing drains,
- 13) Lawn watering runoff,
- 14) Water from individual residential car washing,
- 15) Flows from riparian habitats and wetlands,
- 16) Residual street wash water,
- 17) Discharges or flows from fire-fighting activities, and
- 18) A discharge authorized by a separate National Pollutant Discharge Elimination System (NPDES) permit.

DRAFT

- (a) The Department recommends that stormwater management programs include public education and outreach activities directed at reducing these discharges even if they are not substantial contributors of pollutants to your system.
- b) This permit does not relieve entities that cause illicit discharges, including spills, of oil or hazardous substances, from responsibilities and liabilities under State and Federal law and regulations pertaining to those discharges.
- c) This permit does not authorize a violation of West Virginia State Water Quality Standards (Title 47 CSR Series 2) and West Virginia Ground Water Quality Standards (Title 47 CSR Series 58).

DRAFT

4. Continuation of this General Permit

- a) If this general permit is not reissued or replaced prior to the expiration date, it will be administratively continued in accordance with 47 CSR 10 and remain in force and effect.
- b) If you were authorized to discharge under this general permit prior to the expiration date, any discharges authorized under this permit will automatically remain covered by this general permit until the earliest of:
 - 1) Your authorization for coverage under a reissued general permit,
 - 2) A replacement of this general permit following your timely and appropriate submittal of a complete application requesting authorization to discharge under the new general permit and compliance with the requirements of the new permit,
 - 3) Your submittal of notification that the facility has ceased operations,
 - 4) Issuance or denial of an individual permit for the facility's discharge; or
 - 5) A formal permit decision by the Department not to reissue this general permit, at which time the Department will identify a reasonable time period of covered discharges to seek coverage under an alternative general permit or individual permit.

5. Maximum Extent Practicable (MEP)

- a) The Clean Water Act (CWA §402(p)(3)(B).) states that MS4 permits "shall require controls to reduce the discharge of pollutants to the maximum extent practicable, including management practices, control techniques and system, design and engineering methods."
- b) It is recognized that "pollutant reductions that represent MEP may be different for each small MS4, given the unique local hydrologic and geologic concerns that may exist and the differing possible pollutant control strategies. Therefore, each permittee will determine appropriate BMPs to satisfy each of the six minimum control measures through an evaluative process" (Federal Register, Volume 64, No. 235, page 68754, December 8, 1999.).
- c) This permit shall require the permittee to develop, implement, assess, and enforce a Stormwater Management Program designed to meet the MEP standard.

Part II

A. Notice of Intent (NOI) and SWMP Applications

1. Deadline for Notification

Within thirty (30) days of the effective date of this permit, all owners/operators of small MS4s shall submit a Notice of Intent (NOI) on the form provided in Appendix A of this permit. The NOI shall be submitted via the Department's ePermitting system.

2. Deadline for SWMP

Within six (6) three months of the effective date of this permit, all owner/operators of small MS4s shall submit their SWMP to the Department. The SWMP shall be submitted on the site registration application form provided by the Department.

3. Co-permittees Under a Single NOI

Co-permittees may jointly submit a single NOI provided the SWMP clearly defines individual roles and responsibilities.

4. Where to Submit

DRAFT

NOIs and SWMPs shall be submitted to:

WVDEP - Division of Water and Waste Management
MS4 / NPDES Stormwater Permitting
601 57th Street, SE
Charleston, WV 25304

B. Requirements of SWMP

1. Existing Permittees

Existing permittees must update and continue to implement approved stormwater management program components designed to reduce the discharge of pollutants from small municipal separate storm sewer systems to the maximum extent practicable (MEP), to protect water quality, and satisfy the appropriate requirements of the Clean Water Act.

2. New Permittees

New permittees shall submit a SWMP within (6) six months of the approval of the NOI.

3. Public Notice

In order to meet public notice requirements of NPDES permits, the permittee shall make available to the public, in accordance with Code of State Regulations; Title 47, Series 10, Section 12, the opportunity to comment on MS4 stormwater management programs.

4. Minimum Control Measures

The SWMP must include the minimum control measures described in Section C of this part along with measurable goals and milestones appropriate for each measure and justifications for each milestone. Information about developing measurable goals can be found on the USEPAs website.

5. Extension of Milestones

Subject to the five-year limitation noted below in this paragraph, extension of milestones will be granted for good cause shown. Failure to implement effective best management practices (BMPs) is not good cause to extend milestones.

6. Implementation and Enforcement

The SWMP must also provide details on how new permittees will implement and enforce the program. The terms and conditions of this permit and the new permittee's approved SWMP must be fully implemented, except where noted, within five years of the effective date of this permit. In instances where this permit specifies that the MS4 regulate public projects and facilities, the MS4 is expected to only regulate those entities where they have jurisdiction and/or authority. Existing permittees are to follow the schedules in their approved SWMP.

7. Evaluation

The SWMP shall include an ongoing program for gathering, tracking, maintaining, and using information to evaluate the stormwater management program development, implementation and permit compliance.

DRAFT

8. BMPs for Discharges to 303d and TMDL Receiving Waters

If the permittee's small MS4 discharges into waters listed on the Clean Water Act Section 303(d) list of impaired waters or waters with an approved Total Maximum Daily Load (TMDL), the SWMP must document how the proposed BMPs will control the discharge of the pollutants of concern.

9. Wasteload Allocations

Permittees discharging to waters with an approved TMDL shall meet the applicable wasteload allocations of that TMDL.

10. Annual Report

An annual report shall be submitted to Director each year on the anniversary of the SWMP approval.

C. Stormwater Management Program for Small MS4s

1. Best Management Practices

Permittees shall implement and continue BMPs specific to current SWMPs until revisions are authorized by the Director.

2. Implementation

DRAFT

New permittees should begin implementation of the terms and conditions of this permit as soon as this permit becomes effective, as full implementation is required within five years. Existing permittees must comply with previously approved schedules.

3. Coordination Among Permittees

Coordination among permittees may be necessary to comply with certain conditions of the SWMP. The SWMP shall include appropriate coordination mechanisms among permittees to encourage effective stormwater related policies, programs and projects within adjoining or shared areas. Potential permittees include but are not limited to municipalities, transportation agencies, universities, colleges, hospitals, prisons, and military bases.

4. Relying on Others

The SWMP shall include all components described in Part II, Sections B and C. In accordance with 40 CFR 122.35(a), a permittee may rely on another entity to implement one or more of the components in this section, provided that entity is fully disclosed in the SWMP.

5. Roles and Responsibilities

Coordination mechanisms shall specify roles and responsibilities for the control of stormwater and its associated pollutants between physically interconnected MS4s covered by the small MS4 general permit.

6. Discharges to Common Water Bodies

Coordination mechanisms shall reflect stormwater management for permittees discharging into common water bodies, with the goal of avoiding conflicting plans, policies and regulations.

7. Minimum Control Measures

a) Public Education and Outreach

- 1) The SWMP shall include an education and outreach program aimed at reducing or eliminating behaviors and practices that cause or contribute to adverse stormwater impacts.
- 2) The program shall target residents, businesses, industries, elected officials, policy makers, planning staff, and the permittee's staff and employees and contractors.

- 3) The education program may be developed locally or regionally.
- 4) As a minimum performance measure, existing permittees shall continue to implement previously approved education and outreach programs, and
- 5) The outreach program shall be designed to achieve measurable improvements in the target audience's understanding of stormwater pollution and actions that will reduce its impacts.
 - (a) The permittee may demonstrate improvements to the audience's understanding by reporting behavioral changes. For example only, the reduction of instances of stream littering or citizen efforts made toward stream-bank restoration may be cited.
- 6) Newly permitted MS4s shall establish and begin implementation of education and outreach programs within six months of SWMP approval.
- 7) Education and outreach efforts targeting the general public will be focused on:
 - (a) General impacts of stormwater flows into surface waters.
 - (b) Impacts from impervious surfaces.
 - (c) Source control BMPs and environmental stewardship actions and opportunities in the areas of pet waste, vehicle maintenance, landscaping, and rain water reuse.
- 8) Education and outreach efforts targeting businesses, including home-based and mobile businesses should focus on pollutants most likely associated with the particular business as well as:
 - (a) BMPs for use and storage of products used in vehicular operation, care, or repair, such as petroleum, cleaning supplies and wastes, carwash soaps, and related materials or wastes,
 - (b) Impacts of illicit discharges and spill reporting procedures
- 9) Education and outreach efforts targeting homeowners, landscapers and property managers should focus on:
 - (a) Yard care techniques that protect water quality,
 - (b) BMPs for use and storage of pesticides and fertilizers,
 - (c) BMPs for carpet cleaning and auto repair and maintenance,
 - (d) Runoff reduction techniques, including site design, pervious paving, and retention of forests and mature trees, and
 - (e) Stormwater pond maintenance.

DRAFT

- 10) Education and outreach efforts targeting engineers, contractors, developers, review staff and land use planners should address:
 - (a) Technical standards for construction site sediment and erosion control,
 - (b) Runoff reduction techniques, including site design, pervious pavement, alternative parking lot design, retention of forests and mature trees,
 - (c) Stormwater treatment and flow control BMPs,
 - (d) Impacts of increased stormwater flows into receiving water bodies.
- 11) The permittee shall track and maintain records of public education and outreach activities.
- 12) The SWMP shall clearly show how the Education and Outreach program will be evaluated for effectiveness.
- 13) The permittee is expected to use the evaluation to effectively direct future educational resources.

b) Public Involvement and Participation

DRAFT

- 1) The permittee shall offer opportunities to the public to participate in stormwater management by promoting groups such as advisory councils, watershed associations, or committees to foster input in developing rate structures, stewardship programs, environmental or similar activities.
- 2) Public participation opportunities should provide educational and volunteer programs such as streambank stabilization, riparian planting, volunteer monitoring programs, storm drain marking or stream cleanup programs.
- 3) Permittees shall create opportunities for the public to participate in the decision making processes for developing, implementing and updating the SWMP.
- 4) Each permittee shall develop and implement a process for consideration of public comments on their SWMP.
- 5) The SWMP is to list a method of routine communication to notify public groups of upcoming opportunities such as recycling events or stream bank stabilization projects.

c) Illicit Discharge Detection and Elimination (IDDE)

- 1) The permittee shall develop, implement, assess, and enforce an ongoing program to prohibit improper disposal, detect and remove illicit connections, and eliminate illicit discharges to the storm sewer system .
- 2) The permittee shall develop a response procedure for spills not under the purview of another responding authority.

- 3) New permittees shall establish and begin implementation of these requirements within one year of SWMP approval.
- 4) Storm sewer system maps shall be updated on an annual basis and shall include:
 - (a) The location of all known storm sewer outfalls,
 - (b) Known connections authorized since map was last updated,
 - (c) Receiving waters,
 - (d) Structural stormwater BMPs owned, operated or maintained by the permittee,
 - (e) The location and type of all other stormwater conveyances located within the boundaries of the MS4 watershed, and
 - (f) Geographic areas outside the permittee's jurisdiction that discharge stormwater into the MS4.
 - (g) The permittee may opt to include land use on the map. **DRAFT**
- 5) Storm sewer system maps shall be maintained at the permittee's office and made available to the public and the Department upon request.
- 6) Any paper maps submitted to the Department shall be a scale of 1" = 500' and on pages sized 24"x 36" or 22"x3 6", folded to 8 x 11 inches.
- 7) Each permittee shall implement a process to annually review and update IDDE Ordinances or other regulatory mechanisms.
- 8) The regulatory mechanism must be as stringent at prohibiting and eliminating pollutant sources from entering the MS4 as allowable under State and Local law.
- 9) The IDDE program shall be adequately funded to fulfill the requirements of this permit.
- 10) The regulatory mechanism does not need to prohibit the following categories of non-stormwater discharges, *unless* they are identified to be significant sources of pollutants to waters of the State:
 - (a) Diverted stream flows,
 - (b) Rising ground waters,
 - (c) Uncontaminated ground water infiltration as defined at 40 CFR 35.2005(20),
 - (d) Uncontaminated pumped groundwater,
 - (e) Foundation drains,

DRAFT

- (f) Air conditioning condensation,
 - (g) Irrigation water from agricultural sources,
 - (h) Springs,
 - (i) Water from crawl space sump pumps,
 - (j) Footing drains,
 - (k) Flows from riparian habitats and wetlands,
 - (l) Non-stormwater discharges covered by another NPDES permit,
 - (m) Discharges or flows from fire-fighting activities.
- 11) The regulatory mechanism shall prohibit the following categories of non- stormwater discharges *unless* the stated conditions are met:
- (a) Unless de-chlorinated to 0.2 ppm or less, pH adjusted, solids removed, and discharged in a manner that does not cause erosion or sediment to be discharged into the MS4 or receiving waters:
 - (i) Discharges from potable or non-potable water sources,
 - (ii) Hyper-chlorinated water line flushing,
 - (iii) Pipeline hydrostatic test water,
 - (iv) Chlorinated discharges not associated with drinking water shall be de-chlorinated to 0.1ppm. As example only, swimming pool discharges are to comply with this requirement.
 - (b) Unless minimized through public education:
 - (i) Discharges from lawn watering and other irrigation ,
 - (ii) Street, parking lot and sidewalk wash water,
 - (iii) Dust control waters,
 - (iv) External building wash down
 - (c) Unless street sweeping occurs first:
 - (i) Street washwater affected by construction activities.
- 12) The SWMP shall further address any category of discharge above if the discharges are identified as significant sources of pollutants to waters of the State.

- 13)** The permittee shall develop an enforcement strategy and implement the enforcement provisions of the regulatory mechanism.
- 14)** The regulatory mechanism shall include escalating enforcement procedures.
- 15)** The permittee shall document:
- DRAFT**
- (a)** Locations of priority areas likely to have illicit discharges,
 - (b)** Evaluation of land uses associated with business/industrial activities,
 - (i)** The permittee shall develop an inventory of these priority areas.
 - (ii)** The inventory will include a listing of all facilities with above-ground storage tanks that are not covered by an NPDES permit.
 - (iii)** The permittee's first annual report after identifying the locations with above ground tank will include the number of tanks, contents, and address.
 - (iv)** Subsequent annual reports do not need to include previously reported above ground tanks unless the permittee learns of changes at the facility such as tank demolition, construction, a new business type or owner, or a change of tank content.
 - (c)** Previous complaint locations,
 - (d)** Evaluations of the storage of large quantities of materials that could result in spills.
- 16)** Field assessment activities are to include:
- (a)** Inspection of priority outfalls,
 - (b)** Dry weather screening,
 - (c)** Receiving waters shall be prioritized for visual inspection no later than three years from the effective date of this permit, including a field assessment of at least two water bodies.
 - (d)** At a minimum, one field assessment shall be made each year thereafter.
 - (e)** Screening for illicit connections shall be conducted consistent with the manual titled " Illicit Discharge Detection and Elimination: A Guidance Manual for Program Development and Technical Assessments, Center for Watershed Protection, October 2004", or another methodology of comparable effectiveness.
- 17)** The SWMP shall contain procedures for:
- (a)** Characterizing the nature of and potential public or environmental threat posed by illicit discharges found by or reported to the Permittee and,

- (b) Procedures for evaluating discharges which must be immediately contained and the steps to contain the discharge.
- 18) The SWMP shall contain procedures for:
- (a) Investigating any information suggesting pollution within fifteen (15) days,
 - (i) The investigation shall be designed to determine the source of the discharge or connection, the nature and volume of discharge through the connection, and the party responsible for the connection.
 - (ii) The permittee shall establish a prioritization system for response and verification of the elimination of illicit connections.
 - (iii) The permittee shall assign a higher priority on illicit connections that pose an imminent threat to water quality.
 - (b) Immediately investigating emergencies cases,
 - (c) Referring pollution reports to the Director if imminent water quality impairments are deemed severe or urgent.
- 19) The SWMP shall detail the procedures for tracing the source of illicit discharges such as visual inspections, opening manholes, using mobile cameras, collecting and analyzing water samples.
- 20) The SWMP shall describe the procedures for removing the source of illicit discharges, notifications to appropriate authorities, property owner, business operator and follow up inspections.
- 21) For discharges not eliminated in a timely manner, the SWMP shall detail escalating enforcement and legal actions the Permittee will follow in an effort to end the discharge.
- 22) Permittees shall inform public employees, businesses, and the general public of the hazards associated with illegal discharges and improper disposal of waste.
- 23) The Permittee shall publicly list and publicize a hotline or other local telephone number for public reporting of spills and other illicit discharges.
- 24) The SWMP will describe the permittee's recording keeping system for IDDE calls received and follow-up actions taken to eliminate pollution.
- 25) Permittees shall provide appropriate training to all municipal field staff who are responsible for identification, investigation, termination, cleanup, and reporting of illicit discharges, including spills, improper disposal and illicit connections.

- (a) Follow up training shall be provided annually for changes in procedures, techniques, or requirements.
 - (b) Additionally, staff who are not directly responsible for IDDE but who are likely to come into contact with illicit discharges are to be trained to identify and report such discharges to the permittee's group responsible for follow up.
- 26) Permittees shall document and maintain records of the training provided to specific staff.
- 27) The permittee will track, summarize, and report on an annual basis:
- (a) The number and type of spills or illicit discharges identified during the reporting year,
 - (b) Routine inspections,
 - (c) Investigatory inspections,
 - (d) Feedback received from IDDE public education efforts such as hazard information, and
 - (e) Program evaluation results.

DRAFT

d) Controlling Runoff from Construction Sites

- 1) The permittee shall develop, implement, assess, and enforce a program to reduce pollutants in stormwater runoff from construction site activities that result in a land disturbance of one acre or greater or less than an acre if part of a larger common plan of development or sale.
- 2) Permittees may opt to include construction sites that are less than one acre.
- 3) New permittees shall *begin* implementation of these requirements within 12 (twelve) months of the approval of the SWMP.
- 4) Permittees shall regularly review and update ordinances or other regulatory mechanisms that address stormwater runoff from construction sites.
- 5) The regulatory mechanism shall authorize the permittee to:
 - (a) Implement erosion and sediment control BMPs that are consistent with West Virginia's Erosion and Sediment Control BMP Manual or other manuals listed in Appendix D,
 - (b) Require construction site operators to install and maintain adequate erosion and sediment control BMPs to provide protection to receiving waters,
 - (c) Require construction site operators to control waste such as discarded building materials, concrete truck washout, chemicals, litter, and sanitary waste at the construction site,

- (d) Demonstrate that registration under the WV/NPDES construction stormwater general permit has been obtained for those sites one acre and greater.
 - (i) Provided the Department has approved the permittee as a Qualifying Local Program, WV/NPDES construction stormwater permit will be issued by the permittee and not by the Department.
 - (e) Incorporate consideration of potential water quality impacts and review of individual pre-construction site plans to ensure consistency with local and State sediment and erosion control requirements.
 - (f) Establish authority for receipt and consideration of comments and information submitted by the public.
 - (g) Establish authority for site inspections and enforcement of control measures including steps to identify priority sites for inspection and enforcement based on the nature of the construction activity, topography, and the characteristics of soils and receiving water quality.
- 7) The permittee shall provide adequate funding for site inspections and enforcement of control measures.
- 8) The SWMP will describe educational and training measures for construction site operators including how to prepare a stormwater pollution prevention plan for construction sites within the jurisdiction of the permittee.
- 10) The plan review, inspection and enforcement procedures will address private sector and public sector construction sites.
- 11) The following elements shall be incorporated into the construction site run-off program:
- (a) Coordination of plan review within the permittee's various departments,
 - (b) Procedures for inspecting permitted sites during construction to verify proper installation and maintenance of erosion and sediment controls,
 - (c) Educational and training measures for construction site operators and the permittee's staff, and
 - (d) An enforcement strategy to respond to issues of non-compliance.
- 12) The permittee will develop an application process whereby the construction site operator will describe the sediment and erosion control measures to be taken on the site.

DRAFT

- (a) This application process can include submittal of the stormwater pollution prevention plan that was used to obtain registration under DWWM WV/NPDES construction stormwater permit.
 - (b) The application shall include a listing of all water bodies into which the construction site will discharge and whether or not those water bodies are on the 303(d) list for impaired waters or have established TMDLs.
- 13) The permittee will develop a procedure for keeping records of all regulated construction activities, inspection reports, warning letters, and enforcement documentation.
- 14) A summary of inspection and enforcement activities shall be included in the annual report.

e) **Controlling Runoff from New Development and Redevelopment**

DRAFT

- 1) Permittees shall develop, implement, assess, and enforce an ongoing program to reduce pollutants in stormwater runoff from new development and development activities.
- 2) The program shall provide long-term stormwater controls to protect the physical, chemical and biological integrity of receiving waters and their designated uses from the impacts of stormwater discharges.
- 3) The program shall be applied to all sites that disturb a land area one acre or greater, including projects less than one acre that are part of a larger common plan of development or sale.
- 4) The program shall apply to private sector and public sector development, including roads.
- 5) The program must ensure that controls are in place that will increase groundwater recharge of stormwater runoff where and when possible and protect water quality and reduce the discharge of pollutants.
- 6) Except where otherwise stated, newly permitted MS4s shall *begin* implementation of the requirements contained in this minimum control measure within two years after the approval date of their SWMP.
- 7) The following watershed protection elements are to be used to manage the impacts of stormwater on receiving waters that occur because of regional or watershed- scale management decisions and must, except where noted:
 - (a) Minimize the amount of impervious surfaces (roads, parking lots, roofs, etc.) within each watershed, by minimizing the creation, extension, and widening of parking lots, roads, and associated development.

- (b) Preserve, protect, create and restore ecologically sensitive areas that provide water quality benefits and serve critical watershed functions. These areas may include, but are not limited to; riparian corridors, headwaters, floodplains and wetlands.
 - (c) Implement stormwater management practices that prevent or reduce thermal impacts to streams, including requiring vegetated buffers along waterways, and disconnecting discharges to surface waters from impervious surfaces such as parking lots.
 - (d) Seek to avoid or prevent hydromodification of streams and other water bodies caused by development, including roads, highways, and bridges.
 - (e) Implement standards to protect trees, and other vegetation with important evapotranspirative qualities.
 - (f) Implement policies to protect native soils, prevent topsoil stripping, and prevent compaction of soils.
- 8) The permittee shall incorporate watershed protection elements into the subdivision ordinance or equivalent document.
- (a) The permittee shall incorporate watershed protection elements into all relevant policy and/or planning documents during regular reviews.
 - (b) If a relevant planning document is not scheduled for review during the term of this permit, the permittee must identify the elements that cannot be implemented until that document is revised, and include in the SWMP a schedule for incorporation and implementation that cannot exceed 2 (two) years from the effective date of this permit.
 - (c) Planning documents may include comprehensive or master plans, subdivision ordinances, general land use plans, zoning codes, transportation master plans, specific area plans such as sector plans, site area plans, corridor plans, or unified development ordinances.
- 9) New permittees shall develop quantifiable objectives including a time frame for developing, implementing, assessing, and enforcing each watershed protection element.
- (a) Short-term objectives shall be identified in the SWMP as those that can be accomplished in less than five years
 - (b) Long-term objectives shall be identified in the SWMP as those that will take longer than five years to accomplish.
- 10) Annual reports must include status of implementation of these elements.
- (a) The report will list which planning documents have incorporated the elements and which have yet to do so.

DRAFT

DRAFT

- (viii) Green roofs,
- (ix) Rooftop disconnections, such as gutter drains,
- (x) Permeable pavers/pavement,
- (xi) Porous concrete,
- (xii) Engineered infiltration including extended infiltration via bioretention cells with eventual release,
- (xiii) Release to groundwater may require an Underground Injection Control Permit and permittees are required to list projects using this practice in the annual report,
- (xiv) Or any combination of these methods.

(d) In instances where alternatives to complete on-site retention of the first inch of rainfall are allowed, technical justification as to the infeasibility of on-site retention is required and must be documented.

12) The program shall require all new and redevelopment projects to control stormwater discharge rates, volumes, velocities, durations and temperatures.

13) When considered at the watershed scale, certain types of development can either reduce existing impervious surfaces, or at least create less 'accessory' impervious surfaces.

(a) Incentive standards may be applied to these types of projects.

(b) A reduction of 0.2 inches from the one inch runoff reduction standard may be applied to any of the following types of development:

(i) Redevelopment,

(ii) Brownfield redevelopment

(iii) High density (>7 units per acre)

(iv) Vertical Density, (Floor to Area Ratio (FAR) of 2 or >18 units per acre)

(v) Mixed use and Transit Oriented Development (within ½ mile of transit)

(c) Reductions are additive up to a maximum reduction of .75 inches for a project that meets four or more criteria.

(d) The permittee may choose to be more restrictive and allow a reduction of less than 0.75 inches if they choose.

(e) In no case will the reduction be greater than 0.75 inches.

14) The permittee shall implement, assess, and enforce site and neighborhood design elements in accordance with the approved SWMP schedule.

15) For projects that cannot meet 100% of the runoff reduction requirement on site, the permittee may allow an alternative approach for off-site mitigation, payment in lieu, or for another method of capturing or treating the subject first 1" stormwater.

(a) Prior to allowing an alternative, the permittee must develop, implement, assess, and enforce criteria that can be consistently applied.

(b) The permittee's SWMP must be modified and approved by the Director and the governing body to allow for approval of alternative approaches.

(c) The permittee must develop and apply criteria for determining the circumstances under which these alternatives will be approved.

(d) A determination to allow an alternative to on-site stormwater retention and treatment may be based on the difficulty or cost of implementing measures. For example only:

(i) Too small a lot outside of the building footprint to create the necessary infiltrative capacity even with amended soils;

(ii) Soil instability as documented by a thorough geotechnical analysis;

(iii) A site use that is inconsistent with capture and reuse of stormwater;

(iv) Too much shade or other physical conditions that preclude adequate use of plants.

(e) When allowing either alternative, the permittee must require technical justification as to the infeasibility of on-site management of the first 1" of rainfall.

(f) If, as demonstrated to the permittee, it is technically infeasible to manage on site a portion or all of the subject 1" of rainfall, off site mitigation, payment in lieu, or another approved alternative approach will be applied at a 1:1 ratio for that portion.

(g) For any of these options to be available, the permittee must create an inventory of appropriate mitigation projects, and develop appropriate institutional standards and management systems to value, evaluate and track transactions.

(h) For off-site mitigation projects, runoff reduction practices may be implemented at another location in the same sewershed/watershed as the original project approved by the permittee.

- (i) The permittee shall identify priority areas within the sewershed - watershed in which mitigation projects can be completed.
 - (ii) Mitigation must be for retrofit or redevelopment projects, and cannot be applied to new development.
 - (iii) The permittee shall determine who will be responsible for long term maintenance on mitigation projects.

- (i) For payment in lieu projects, payment may be made to the permittee, who is to apply the funds to a public stormwater project.
 - (i) Permittees shall maintain a publicly accessible inventory of approved in-lieu projects which fully details all monetary transactions associated with the projects.

- (j) Runoff reduction practices shall be applied to redevelopment projects for existing streets or parking lots that are greater than 5000 square feet in size unless otherwise justified.
 - (i) These requirements apply only to projects begun after the effective date of this permit.
 - (ii) The permittee shall document the reasons why a project of this type is not to be included in run-off reduction efforts, to include right-of-way restrictions such as interference with buried utilities, safety concerns such as fire equipment access, traffic control, or other major obstacles.
 - (iii) The permittee will report on any such project annually and include the justification for those without runoff reduction practices applied.

- (k) To ensure that all new development and redevelopment projects conform to the long-term stormwater control standards, the permittee shall develop project review, approval and enforcement procedures.

- (l) The review, approval and enforcement procedures shall apply at a minimum to all new development and redevelopment disturbing greater than or equal to one acre, including projects less than one acre that are part of a larger common plan of development or sale, and shall include:
 - (i) Requirements to submit for review and approval a pre-application concept plan that describes how the performance standards will be met,
 - (ii) A pre-application meeting attended by a project land owner or developer, the project design engineer, and municipal planning staff to discuss conceptual designs may also meet this requirement,
 - (iii) Development of procedures for the site plan review and approval to include inter-departmental consultations, as needed, and a required re-approval process when changes to an approved plan are desired,

DRAFT

- (iv) A requirement for submittal of 'as-built' certifications within 90 days of completion of a project,
 - (v) A post-construction verification process to ensure that stormwater standards are being met, that includes enforceable procedures for bringing noncompliant projects into compliance, and
 - (vi) A description of a program to educate both internal staff and external project proponents of the requirements of long-term stormwater controls.
- (m) The permittee shall require that all developments subject to long-term stormwater controls develop a maintenance agreement and maintenance plan for approved stormwater management practices.
- (n) The permittee shall require that property owners or operators provide verification of maintenance for the approved stormwater management practices.
- (o) Verification shall include one or more of the following as applicable:
- (i) The owner/developer's signed statement accepting responsibility for maintenance until the maintenance responsibility is legally transferred to another party; and/or
 - (ii) Written conditions in the sales or lease agreement that require the recipient to assume responsibility for maintenance; and/or
 - (iii) Written conditions in project conditions, covenants and restrictions for residential properties assigning maintenance responsibilities to a home owner's association or other appropriate group for maintenance of structural and treatment control stormwater management practices; and/or
 - (iv) Any other legally enforceable agreement that assigns permanent responsibility for maintenance of structural or treatment control stormwater management practices.
 - (v) These agreements shall allow the permittee, or designee, to conduct inspections of the stormwater management practices,
 - (vi) The agreement shall account for transfer of responsibility in appropriate legal documents.
- (p) The Ordinance or other regulatory mechanism shall include at a minimum at least one of the following methods for ensuring privately-owned stormwater structures are properly maintained:
- (i) The permittee may enter onto the property, conduct maintenance corrective actions on stormwater structures, and recoup associated costs,

DRAFT

- (ii) The permittee may take enforcement actions against the party responsible for maintaining stormwater structures, to include fines or penalties authorized by the regulatory mechanism, or
 - (iii) The permittee may carry out a legal action against the responsible party in a court having jurisdiction over matters of this type.
 - (iv) The regulatory mechanism shall clearly state that the permittee shall take one of the above actions when the necessary maintenance has not been performed within 30 (thirty) days of notification by the permittee.
- (q) The permittee shall develop and utilize a system to track stormwater management practices at new development and redevelopment projects.
 - (i) Tracking of stormwater management practices shall begin during the plan review and approval process with a database or geographic information system (GIS).
 - (ii) The database or tracking system shall include information on both public and private sector projects that are within the Permittee's jurisdiction .
 - (iii) In addition to the standard information collected for all projects (such as project name, owner, location, start/end date, etc.), the tracking system shall also include:
 - (a) Source control stormwater management practices (type, number, design or performance specifications)
 - (b) Treatment control stormwater management practices (type, number, design or performance specifications)
 - (c) Latitude and longitude coordinates of stormwater BMP controls using a global positioning system
 - (d) Digital photographs of stormwater management practice controls
 - (e) Maintenance requirements of stormwater management practices (frequency of required maintenance and inspections)
 - (f) Inspection information (date, findings, follow up activities, compliance status)
- (r) The permittee shall inspect Stormwater BMPs to determine proper operation and maintenance on the part of the owner/operator.
 - (i) The permittee is to develop an inspection calendar for all stormwater BMPs to be inspected at least once during the permit cycle.
 - (ii) Complete inspection reports shall include:

DRAFT

DRAFT

- (a)** Facility type,
 - (b)** Inspection date,
 - (c)** Name and signature of inspector,
 - (d)** GIS location and nearest street address,
 - (e)** Management practice ownership information (name, address, phone number, fax, and email),
 - (f)** A description of the stormwater BMP condition including the quality of: vegetation and soils; inlet and outlet channels and structures; embankments, slopes, and safety benches; spillways, weirs, and other control structures; and sediment and debris accumulation in storage and forebay areas as well as in and around inlet and outlet structures,
 - (g)** Photographic documentation of all critical stormwater BMP components, and
 - (h)** Specific maintenance items or violations that need to be corrected by the owner/operator along with deadlines and reinspection dates.
- (s)** The permittee shall develop an enforcement and response plan to ensure stormwater BMPs are properly maintained, to include:
- (i)** The permittee shall promptly notify the stormwater BMP owner or operator of any deficiencies discovered during a maintenance inspection.
 - (ii)** The permittee shall follow its enforcement response plan to ensure that management practices are maintained.
 - (iii)** The permittee must conduct a subsequent inspection to ensure completion of all required repairs.
 - (iv)** Procedures to enforce correction orders and a contingency plan if correction orders are not followed through by the responsible party.
- (t)** The permittee shall demonstrate compliance with the requirements for post construction controls by summarizing the following in the Annual Report:
- (i)** A description of how the permittee's legal authority addresses the watershed protection elements ,
 - (ii)** A summary of the number and types of projects that the permittee reviewed for new and development considerations,

DRAFT

- (iii) A summary of the number and types of stormwater BMPs approved in new and redevelopment projects, including the number of approved projects that qualified for incentives and or alternatives authorized by this permit,
- (iv) A summary of the number and types of maintenance agreements approved,
- (v) A summary of stormwater BMP maintenance inspections conducted by the permittee, including a summary of the number requiring maintenance or repair, the number brought into compliance and the number of enforcement actions taken,
- (vi) A summary of any evaluation data collected for long-term stormwater controls, including water quality information, stormwater BMP performance, and model results.
- (u) The permittee shall conduct an assessment of current street design guidelines and parking requirements that affect the creation of impervious cover with the third year annual report.
 - (i) The assessment shall include recommendations and proposed schedules for incorporating policies and standards into relevant documents and procedures to maximize vegetation and to minimize impervious cover attributable to parking and street designs.
 - (ii) The local planning commission and the local transportation commission should be involved in the assessment.
- 16) The permittee shall designate projects with reasonable potential for pollutant loadings as Hot Spots. Water quality treatment practices will be provided prior to infiltration or discharge and will be designed for the specific pollutant and source, for example only, petroleum hydrocarbons at a vehicle fueling island.
 - (a) A project that is a potential hot spot with reasonable potential for pollutant loading(s) that cannot implement adequate preventive or water quality treatment measures to ensure compliance with groundwater and/or surface water quality standards, must properly convey stormwater to a NPDES-permitted wastewater treatment facility or via a licensed waste hauler to a permitted treatment and disposal facility.
 - (b) A project that discharges or proposes to discharge to any surface water or ground water that is used as a source of drinking water must comply with all applicable requirements relating to source water protection.

f) Pollution Prevention & Good Housekeeping for Municipal Operations

- 1) Each existing permittee shall continue to implement good housekeeping and operation and maintenance programs at municipal facilities, including waste water treatment facilities, potable drinking water facilities, municipal fleet operations, maintenance garages, parks and recreation areas, street and infrastructure maintenance, and grounds maintenance operations.
- 2) New permittees have 1 (one) year from the approval date of the SWMP to develop and begin implementation of good housekeeping and operation and maintenance programs at municipal facilities.
- 3) The goal of these programs shall be to prevent or reduce polluted runoff from municipal operations.
- 4) Each permittee shall develop and establish maintenance standards at all municipal facilities that will help protect the physical, chemical and biological integrity of receiving waters.
- 5) The permittee shall establish a schedule of no less than once per calendar year for performing inspections to determine if maintenance standards are being met.
- 6) Each permittee shall track inspections and keep maintenance records for all municipal facilities.
- 7) The SWMP will describe policies and procedures the permittee will utilize to reduce the discharge of pollutants in stormwater runoff from all lands owned or maintained by the permittee and subject to this permit, including but not limited to: parks, open space, road right-of-way, maintenance yards, water/sewer infrastructure and stormwater treatment and flow practices.
 - (a) These policies and procedures shall, at a minimum, address:
 - (i) Application of fertilizer, pesticides, and herbicides including the development of nutrient management and integrated pest management plans,
 - (ii) Sediment and erosion control,
 - (iii) Landscape maintenance and vegetation disposal,
 - (iv) Trash management,
 - (v) Building exterior cleaning and maintenance,
 - (vi) Chemical and material storage,
 - (vii) Street sweeping and inlet/catch basin cleaning,

- 8) The program shall include a training component intended to prevent or reduce polluted runoff from municipal operations including, as appropriate:
- (a) Street/sewer and right-of-way construction and maintenance,
 - (b) Water and sewer departments,
 - (c) Parks and recreation department,
 - (d) Municipal water treatment and waste water treatment,
 - (e) Fleet maintenance garage and mechanic crew,
 - (f) Fire departments,
 - (g) Building maintenance and janitorial,
 - (h) Contractors and subcontractors who may be contracted to work in the above described areas,
 - (i) Personnel responsible for answering questions about the permittees stormwater program, this includes persons who may respond to the public about the program,
 - (j) Any other department of the permittee that may impact stormwater run-off.
- 9) Training materials are available from WVDEP, USEPA, or other organizations for use by permittees.
- 10) For employees whose construction, operations, or maintenance job functions may impact water quality, the training program shall address:
- (a) The importance of protecting water quality,
 - (b) The requirements of this general permit,
 - (c) Operation and maintenance standards,
 - (d) Inspection procedures,
 - (e) Selecting appropriate BMPs,
 - (f) Proper task procedures for preventing or minimizing impacts to water quality,
 - (g) Procedures for reporting water quality concerns such as potential illicit discharges,
 - (h) Follow-up and refresher training shall be provided at a minimum of once every twelve months and,
 - (i) Shall include any changes in procedures, techniques or requirements.

DRAFT

DRAFT

- 11) Permittees shall maintain training records.
- 12) The SWMP shall identify industrial facilities under the permittee’s control and is to include the location, type of activity, individual WV/NPDES permit number, or registration number if under WV/NPDES Multi-Sector General Water Pollution Control Permit.
- 13) For Industrial facilities not covered under another WV/NPDES permit, the SWMP shall fully disclose the location type of activity, and potential pollutant sources.
- 14) The SWMP shall contain a benchmark monitoring plan for stormwater discharged from facilities or locations of municipal industrial activities.
 - (a) Pollutant concentrations above the benchmark could be detrimental to water quality or may adversely affect human health from ingestion of water or fish.
 - (b) Pollutant concentrations below the benchmark are to be viewed by the Permittee as indicating little potential for water quality concern.
 - (c) Levels above the benchmark shall trigger a review of the SWMP by the permittee to determine if alternative, more effective BMPs can be implemented. Reviews must be conducted within 30 days of the permittee’s receipt of the laboratory or field results of stormwater analysis.
 - (d) The following parameters should be considered and incorporated as appropriate for municipal industrial activities:

<u>Parameter</u>	<u>Cut-off Concentration</u>	<u>Measurement</u>
BOD-5	30 mg/l	Once/Six months
COD	120 mg/l	Once/Six months
TSS	100 mg/l	Once/Six months
Ammonia Nitrogen	4 mg/l	Once/Six months
Oil & Grease	15 mg/l	Once/Six months
pH	6.0 – 9.00 s.u.	Once/Six months

- (e) Permittees that receive discharges into their small MS4 from their sewage treatment works must, in addition to the above listed monitoring requirements, also meet the following monitoring requirements for those discharges:

<u>Parameter</u>	<u>Cut-off Concentration</u>	<u>Measurement</u>
Fecal Coliform, General	400 counts/100 ml	Once/Six months

- (f) Permittees that receive discharges into their small MS4 from their facilities that store less than 50,000 tons of salt shall monitor for the following:

<u>Parameter</u>	<u>Cut-off Concentration</u>	<u>Measurement</u>
TSS	100 mg/l	Once/Six months
Chloride	860 mg/l	Once/Six months
Cyanide	Monitor & Report	Once/Six months
Total Iron	1.0 mg/l	Once/Six months

- (g) The permittee’s semi-annual discharge monitoring report start date is determined by the date coverage under this permit was issued and/or reissued.

DRAFT

- (i) Registrations issued/reissued on the first through the fifteenth of a month will use that month to determine the semi-annual reporting date.
 - (ii) Registrations issued after the fifteenth of each month will use the next month to determine the reporting start date.
 - (iii) For permittees whose monitoring is initiated as a result of a modification, the approval date of the modification will be used to determine the discharge monitoring reporting start date, instead of the registration issued date.
 - (iv) All discharge monitoring reporting will require mandatory electronic submission via the Department's eDMR system. The technical requirements for the eDMR process will be an internet connection, an email account, and internet browser software.
 - (v) Permittees that do not have the above requirements and/or are unable to participate in the eDMR process must submit a written explanation to the Department explaining why the process cannot be used.
 - (vi) The Department will review explanations and notify permittees in writing that exemptions are approved or denied.
- 15) Permittees may submit low concentration waivers when the average concentration pollutant calculated from all monitoring data with a minimum of four consecutive samples is less than the corresponding cut-off concentration, additional monitoring for that pollutant is not required.
- (a) The annual report must contain a certification that there has not been a significant change in the industrial activity or the BMPs in the area that drains to the outlet for which sampling was waived.
 - (b) Low concentration waivers are for discharges from industrial facilities or activities only and are not to be utilized for discharges at representative outfalls.
- 16) A condition of no exposure exists at a facility when industrial materials or activities are protected by a storm-resistant shelter to prevent exposure to rain, snowmelt, and/or runoff.
- (a) A storm resistant shelter is not required for drums or barrels that are sealed and do not leak.
 - (i) Sealed means banded or secured and without operational taps or valves.
 - (b) A No Exposure Certification may be for an entire facility or for any portion thereof provided the entire portion draining to a particular outfall has no exposure.
 - (i) For example only, a public works facility might store road salt in a storm-resistant shelter but might have leaky heavy equipment parked in the same drainage area, therefore, No Exposure may not be certified

for the outfall.

- (c) Stormwater samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previous measureable storm event (greater than 0.1 in rainfall).
 - (i) Where semi-annual sampling is required, the samples for each six month period shall be collected at least three months apart.
 - (ii) The grab sample shall be taken during the first thirty minutes of the discharge.
 - (iii) If the collection of a grab sample during the first thirty minutes is impractical, a sample can be taken during the first hour of the discharge, and the discharger shall submit with the monitoring report a description of why a grab sample during the first thirty minutes was impractical.
- (d) Stormwater samples may be collected during routine work hours and on routine work days of the permittee's staff responsible for collection.

DRAFT

A. Sharing Responsibility

1. Permittees may rely on one another to satisfy one or more permit obligations, provided the SWMP contains a clear description of the parties' agreement(s) which must be as stringent as the corresponding permit requirement(s).

- (j) Each party must confirm the terms of the agreement(s) in writing and retain copies of the agreement(s) for the duration of this permit, including any automatic extensions of the permit term.

B. Compliance of Discharge with Water Quality Standards

1. The permittee shall develop, implement, assess, and enforce a SWMP designed to reduce the discharge of pollutants to the maximum extent practicable to protect water quality and to satisfy the appropriate requirements of the Clean Water Act.
2. If stormwater discharges have a reasonable potential to cause or contribute to violations of water quality standards in the receiving water, additional controls are required.
3. Full implementation of selected BMPs using known, available, and reasonable methods of prevention, control, and treatment to prevent and control stormwater pollution from entering waters of the State of West Virginia is considered an acceptable effort to reduce pollutants from the municipal storm drain system to the maximum extent practicable.

C. Requiring an Individual Permit

1. The Department retains the right to require any person authorized by this general permit to instead apply for and obtain an individual WV/NPDES permit, if appropriate.
2. An explanation will be provided to the applicant/permittee, along with the proper application form and due date for submittal of the individual permit application.

D. Discharge to Impaired Waters

1. 303(d) Listed Waters

- a) This permit does not authorize new sources or new discharges of pollutants of concern to impaired waters unless consistent with an approved Total Maximum Daily Load (TMDL) and applicable state law.
- b) Impaired waters are those that do not meet applicable water quality standards. Impaired waters are identified on the West Virginia, Section 303(d) list until a TMDL is developed and approved by USEPA.
- c) Pollutants of concern are those pollutants for which the water body is listed as impaired. A list of impaired water bodies in West Virginia can be found on the Department's website.

- d) The SWMP must describe and demonstrate how selected BMPs will control pollutants of concern from entering 303d listed waters.

2. Discharging into Waters with Approved TMDLs

- a) Within six (6) months of approval of a new TMDL for which the permittee is identified as a stressor, the permittee must modify the SWMP to include BMPs targeting the pollutant of concern.
- b) The SWMP must include a monitoring component for the pollutant of concern and be designed to assess the effectiveness of selected BMPs in achieving the wasteload allocations .
- c) Monitoring may consist of stormwater sampling, in-stream monitoring, or modeling. For more information see the USEPA/State guidance titled: *Evaluating the effectiveness of municipal stormwater programs* and *Understanding Impaired Waters and Total Maximum Daily Load (TMDL) Requirements for Municipal Stormwater Programs*. Both guidance documents can be found on the Department's website.
- d) Monitoring results shall be used to determine if selected BMPs need revised to better comply with wasteload allocations.

E. Endangered and Threatened Species

- 1. To comply with the Federal Endangered Species Act, the permittee will document that the US Fish and Wildlife Service (USFWS) was informed of selected BMPs for discharges to affected waters.
- 2. The permittee is required to expedite SWMP modification upon notice from USFWS for improved BMPs.

DRAFT

Part IV

DRAFT

A. Monitoring, Recordkeeping, Evaluation, Reporting and Program Review

1. Stormwater Monitoring

- a) The permittee shall monitor stormwater from a minimum of one outfall.
- b) If the permittee opts to monitor at just one location, an outfall located in the most densely populated section of the MS4 shall be selected as the representative outfall.
- c) The permittee shall, at a minimum, monitor one outfall for the following parameters:

<u>Parameter</u>	<u>EPA Method No.</u>	<u>Method Detection Limit (mg/l)</u>
Total Kjeldahl Nitrogen	351.2	0.03
Nitrate Nitrogen	300.0	0.002
Nitrite Nitrogen	300.0	0.004
Total Phosphorous	365.4	0.01

- e) The SWMP approval will include a Discharge Monitoring Report Form that will actually list Total Phosphorus and Total Nitrogen as parameters for the representative outfall.
- f) At the time this permit is issued, the USEPA has not approved a method to directly test for Total Nitrogen. The Total Nitrogen value to be reported shall be the sum of the test results for Total Kjeldahl Nitrogen, Nitrate, and Nitrite.
- g) If all three constituents of total nitrogen are not detected at its method detection limit (MDL), the permittee shall sum the actual MDLs for each constituent and report the result as less than the calculation.
- h) When calculating the sum of the constituents for total nitrogen, the permittee shall use actual analytical results when these results are greater than or equal to the MDL for a particular constituent and should use zero (0) for a constituent if one or two of the constituents are less than the MDL.
- i) The methods and detection levels in the table above are recommended to be used unless the permittee desires to use an EPA approved method with a detection level equal to or lower than those specified above.
- j) Registrations issued/reissued on the first through the fifteenth of a month will use the issued month to determine the semi-annual reporting date.

issued month to determine the reporting start date.

- l) For permittees whose monitoring is initiated as a result of a modification, the approval date of the modification will be used to determine the discharge monitoring reporting start date, instead of the registration issued date.
- m) All discharge monitoring reporting will require mandatory electronic submission via the Department's electronic Discharge Monitoring Report (eDMR) system. The technical requirements for the eDMR process will be an internet connection, an email account, and internet browser software.
- n) Permittees that do not have the above requirements and/or are unable to participate in the eDMR process must submit a written explanation to the Department explaining why the process cannot be used.
- o) The Department will review explanations and notify permittees in writing that exemptions are approved or denied.
- p) Stormwater samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previous measureable storm event (greater than 0.1 in rainfall).
 - (i) Where semi-annual sampling is required, the samples for each six month period shall be collected at least three months apart.
 - (ii) The grab sample shall be taken during the first thirty minutes of the discharge.
 - (iii) If the collection of a grab sample during the first thirty minutes is impractical, a sample can be taken during the first hour of the discharge, and the discharger shall submit with the monitoring report a description of why a grab sample during the first thirty minutes was impractical.
- q) Stormwater samples may be collected during routine work hours and on routine work days of the permittee's staff responsible for collection.

DRAFT

2. Recordkeeping and Public Availability of SWMP and Annual Report

- a) The permittee shall keep records to verify compliance with this permit for at least three years beyond the permit expiration date and any continuance as described in Part 1.4.
- b) Records shall be submitted to the Department upon request and released to the public in accordance with the Freedom of Information Act.
- c) The permittee shall make the SWMP and annual report available to the public at reasonable times during regular business hours.
- d) Additionally, the SWMP and annual report shall be posted on the permittees website, or
- e) A permittee without a website may submit the SWMP and annual report in electronic format to the Department for distribution, if requested.

3. Program Evaluation

- a) The permittee shall evaluate the effectiveness of selected BMPs in the approved SWMP to determine compliance with this general permit.
- b) The permittee shall use a sufficient number of known, available, and reasonable methods to evaluate the effectiveness of the SWMP.
- c) Results of the evaluation shall be submitted in the annual report.
- d) Permittees can find additional information about evaluations in the USEPA/States guidance document titled: *Evaluating the Effectiveness of Municipal Stormwater Programs*, which can be found on the Department's website.

4. Annual Report

- a) Annually, the permittee shall submit a report to the Department summarizing:
 - 1) Activities undertaken for each of the minimum control measures,
 - 2) The results of BMP evaluations,
 - 3) The status of compliance with each selected BMP,
 - 4) An overall assessment of the progress toward achieving the identified measurable goals for each of the minimum control measures,
 - 5) Any change to identified goals,
 - 6) Results of information collected and analyzed, including monitoring data, during the annual reporting period which has not been reported through the eDMR process,
 - 7) Any revision to the approved SWMP schedule,
 - 8) A description of the status of the street and parking design assessment;
 - 9) A description of the coordination efforts with other permittees or public entities regarding the implementation of the minimum control measures including the status of any agreement(s) undertaken in accordance with "Sharing Responsibility".
 - 10) A summary of construction site inspections and enforcement activities.
 - 11) A summary of post construction controls approved by the permittee and installed on newly developed sites or redeveloped sites.
 - 12) A description of specific BMPs that were implemented in order to reduce pollutants of concern in impaired receiving waters and waters in which a TMDL has been developed, and

DRAFT

13) A fiscal analysis of capital and operating expenditures to implement the minimum control measures.

14) The fiscal analysis shall include only those expenditures by the permittee and not those for minimum control measures implemented by other entities.

5. Program Review

a) The Department will assess the effectiveness of the SWMP for eliminating non-storm water discharges and reducing the discharge of pollutants to the MEP, by reviewing program implementation and annual reports.

b) Additional periodic evaluations may be conducted to determine compliance with permit conditions.

The permittee must comply with all terms and conditions of this permit. Permit noncompliance constitutes a violation of the federal Clean Water Act (CWA) and State Act, Chapter 22, Article 11 & Article 12 and is grounds for enforcement action; for permit modification, suspension or revocation.

Failure to comply with the terms and conditions of this permit, with the plans and specifications submitted with the site registration application, the most currently approved SWMP, and the appropriate appendices shall constitute grounds for the revocation or suspension of this permit and for the invocation of all the enforcement procedures set forth in Chapter 22, Article 11 of the Code of West Virginia

BY: _____

Scott G. Mandirola
Director

DRAFT

Appendix A

WV/NPDES GENERAL PERMIT NUMBER WV0116025

SMALL MUNICIPAL SEPARATE STORM SEWER SYSTEMS

NOTICE OF INTENT (NOI)

1. MS4 Owner/Operator Information:

Name of public entity that operates a small MS4:

Contact Person: _____ Telephone: _____

E-mail address of contact person: _____

Address: _____

City: _____ State: _____ Zip Code: _____

2. Receiving stream(s): _____

3. Fee - \$17.50 per acre of area served by the applicant. Maximum fee is \$1750.00

Amount enclosed: _____

NOTE:

The Notice of Intent provides MS4 entities initial coverage under the WV/NPDES MS4 General Permit. Stormwater Management Programs plans must be submitted within six months of the issuance date of the General Permit.

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information including the possibility of a fine and imprisonment for knowing violations.

OFFICIAL SIGNATURE _____ DATE _____

PRINT NAME _____

Return To:
WVDEP - DWWM
MS4/NPDES
601 57th Street, SE
Charleston, WV 25304

DRAFT

Appendix B

Definitions

Accessory Impervious Surfaces means those additional impervious surfaces that are created to service new development; including roads, shopping centers, office parks and parking lots.

Best Management Practices (BMP's) means schedules of activities, prohibitions of practices, maintenance procedures, policies, and other management practices to prevent or reduce the pollution of waters of the State of West Virginia. BMP's also include treatment requirements, operating procedures, and practices to control site runoff, spillage or leaks, waste disposal or drainage from material storage. BMP's can include structural as well as non-structural practices.

Bioretention is the water quality and water quantity stormwater management practice using the chemical, biological and physical properties of plants, microbes and soils for the removal of pollution from stormwater runoff.

Canopy Interception is the interception of precipitation, by leaves and branches of trees and vegetation that does not reach the soil.

Clean Water Act (CWA) means Public Law 92-500, as amended by Public Law 95-217, Public Law 97-117 and Public Law 95-576; U.S.C. 1251 et seq.

Common Plan of Development is a contiguous construction project where multiple separate and distinct construction activities may be taking place at different times on different schedules but under one plan. The "plan" is broadly defined as any announcement or piece of documentation or physical demarcation indicating construction activities may occur on a specific plot; included in this definition are most subdivisions and industrial parks.

Cut off concentration is a concentration at which stormwater could potentially impair, or contribute to impairing water quality.

Director means the Director of the Division of Water and Waste Management, West Virginia Department of Environmental Protection, or his/her designated representative.

Engineered Infiltration is an underground device or system designed to accept stormwater and slowly exfiltrates it into the underlying soil. This device or system is designed based on soil tests that define the infiltration rate.

Evaporation means rainfall that is changed or converted into a vapor.

Evapotranspiration means the sum of evaporation and transpiration of water from the earth's surface to the atmosphere. It includes evaporation of liquid or solid water plus the transpiration from plants.

Extended Filtration is a structural stormwater practice which filters stormwater runoff through vegetation and engineered soil media. A portion of the stormwater runoff drains into an underdrain system which slowly releases it after the storm is over.

DRAFT

Hot Spot A project is a potential hot spot with reasonable potential for pollutant loading must provide water quality treatment for associated pollutants before infiltration. For example, spillages from a vehicle fueling station might contaminate stormwater and should therefore be directed to an oil/water separator before infiltration. Man made structures that convey stormwater underground may require an Underground Injection Control Permit.

Hydromodification means the alteration of the natural flow of water through a landscape, and often takes the form of channel straightening, widening, deepening, or relocating existing, natural stream channels. It can also involve excavation of borrow pits or canals, building of levees, streambank erosion, or other conditions or practices that change the depth, width or location of waterways. Hydromodification usually results in water quality and habitat impacts.

The U.S. Environmental Protection Agency (EPA) has defined hydromodification as the "alteration of the hydrologic characteristics of coastal and non-coastal waters, which in turn could cause degradation of water resources."¹¹

Illicit Discharge means any non-permitted discharge to a regulated small MS4 or to waters of the State of West Virginia that does not consist entirely of stormwater or authorized non-stormwater discharges covered under a NPDES permit.

Infiltration is the process by which stormwater penetrates into soil.

Land Use means the way in which land is used, especially in farming and municipal planning.

Maintenance Agreement means a formal agreement or contract between a local government and a property owner designed to guarantee that specific maintenance functions are performed.

Municipal Field Staff means employees of the municipality and its departments that spend a portion of their employment in the marketplace, outside of the company office.

Municipal Separate Storm Sewer System (MS4) means conveyances for stormwater, including, but not limited to, roads with drainage systems, municipal streets, catch basins, curbs, gutters, ditches, human made channels or storm drains owned or operated by any municipality, sewer or sewage board, State agency or Federal agency or other public entity that discharges directly to surface waters of the State of West Virginia.

Municipal Staff means employees of the municipality and its departments.

Notice of Intent (NOI) means a notification of intent to seek coverage under this general permit, to discharge stormwater into waters of the State of West Virginia.

NPDES means National Pollutant Discharge Elimination System, a provision of the Clean Water Act which prohibits the discharge of pollutants into waters of the United States. This federally mandated permit program is used for regulating point source discharges.

Outfall means the point source where the MS4 discharges from a pipe, ditch or other discreet conveyance directly or indirectly to water of the State of West Virginia, or to another MS4.

Planning documents are documents a municipality or jurisdiction uses for planning. They include, but are not limited to; comprehensive or master plans, subdivision ordinances, general land use plan, zoning

DRAFT

code, transportation master plan, specific area plans, such as sector plan, site area plans, corridor plans, or unified development ordinances.

Pollutants of Concern are those pollutants which cause a water body to be placed on the Section 303(d) list of impaired waters.

Qualifying Local Program means a WV DEP formally recognized state, municipal or county program that meets or exceeds the provisions of WV DEP stormwater construction program in accordance with 40 CFR 122.44(s).

Rainfall and Rainwater Harvesting is the collection, conveyance, and storage of rainwater. The scope, method, technologies, system complexity, purpose, and end uses vary from rain barrels for garden irrigation in urban areas, to large-scale collection of rainwater for all domestic uses.

Receiving waters or receiving water means the ‘water resources’ that receive the discharge from the permittee.

Runoff Reduction practices and/or techniques are the collective assortment of stormwater practices that reduce the volume of stormwater from discharging off site. These include stormwater practices that infiltrate, evapotranspire and reuse stormwater on site.

Secretary means the Secretary of the West Virginia Department of Environmental Protection, or his/her designated representative.

Site Registration Application means the forms designed by the Director for the purpose of obtaining coverage under the small MS4 general permit. The information contained on the site registration application once approved becomes the “stormwater management program” for the permittee.

Soil amendments are components added to in situ or native soils to increase the spacing between soil particles so that the soil can absorb and hold more moisture. The amendment of soils changes various other physical, chemical and biological characteristics so that the soils become more effective in maintaining water quality.

Source control stormwater management means practices that control stormwater *before* pollutants have been introduced into stormwater.

Stormwater Hotspots are commercial, industrial, institutional, municipal, or transportation related operations that may produce higher levels of stormwater pollutants, and/or present a higher potential risk for spills, leaks, or illicit discharges. Hotspots may include: gas stations, petroleum wholesalers, vehicle maintenance and repair, auto recyclers, recycling centers and scrap yards, landfills, solid waste facilities, wastewater treatment plants, airports, railroad stations and associated maintenance facilities, and highway maintenance facilities.

Stormwater Pollution Prevention Plan (SWPPP) means the erosion and sediment control plan for a construction site.

Stormwater Management Practice means practices that manage stormwater, including structural and vegetative components of a stormwater system.

Total Maximum Daily Load (TMDL): A calculation of the maximum amount of a pollutant that a waterbody can receive and still meet water quality standards. A TMDL is the sum of individual wasteload

allocations for point sources (WLA), load allocations for nonpoint sources and natural background (LA), and must consider seasonal variation and include a margin of safety. The TMDL comes in the form of a technical document or plan. (40 CFR 130.2 and 130.7)

Treatment control stormwater management means practices that ‘treat’ stormwater after pollutants have been incorporated into the stormwater.

Wasteload allocation (WLA): The portion of a receiving water’s loading capacity that is allocated to one of its existing or future point sources of pollution. WLAs constitute a type of water quality-based effluent limitation (40 CFR 130.2(h)).

Water Quality Treatment means any passive or active process that removes pollutants from stormwater, and/or prevents pollutants from encountering stormwater.

Water Resources, ‘Water’ or ‘Waters’ means any and all water on or beneath the surface of the ground, whether percolating, standing, diffused or flowing, wholly or partially within this state, or bordering this state and within its jurisdiction, and includes, without limiting the generality of the foregoing, natural or artificial lakes, rivers, streams, creeks, branches, brooks, ponds (except farm ponds, industrial settling basins and ponds and water treatment facilities), impounding reservoirs, springs, wells, watercourses and wetlands.

DRAFT

Appendix C

I. MANAGEMENT CONDITIONS:

1. Duty to Comply

a) The permittee must comply with all conditions of this permit. Permit noncompliance constitutes a violation of the CWA and State Act and is grounds for enforcement action; for permit modification, revocation and reissuance, suspension or revocation; or for denial of a permit renewal application.

b) The permittee shall comply with all effluent standards or prohibitions established under Section 307(a) of the CWA for toxic pollutants within the time provided in the regulations that establish these standards or prohibitions, even if the permit has not yet been modified to incorporate the requirement.

2. Duty to Reapply

If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for a new permit at least 180 days prior to expiration of the permit.

3. Duty to Mitigate

The permittee shall take all reasonable steps to minimize or prevent any discharge in violation of this permit, which has a reasonable likelihood of adversely affecting human health or the environment.

4. Permit Actions

This permit may be modified, revoked and reissued, suspended, or revoked for cause. The filing of a request by the permittee for permit modification, revocation and reissuance, or revocation, or a notification of planned changes or anticipated noncompliance, does not stay any permit condition.

5. Property Rights

This permit does not convey any property rights of any sort or any exclusive privilege.

6. Signatory Requirements

All applications, reports, or information submitted to the Chief shall be signed and certified as required in Title 47, Series 10, Section 4.6 of the West Virginia Legislative Rules.

7. Transfers

This permit is not transferable to any person except after notice to the Chief. The Chief may require modification or revocation and reissuance of the permit to change the name of the permittee and incorporate such other requirements as may be necessary.

8. Duty to Provide Information

The permittee shall furnish to the Chief, within a reasonable specified time, any information which the Chief may request to determine whether cause exists for modifying, revoking and reissuing, suspending, or revoking this permit, or to determine compliance with this permit. The permittee shall also furnish to the Chief, upon request, copies of records required to be kept by this permit.

9. Other Information

Where the permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or in any report to the Chief, it shall promptly submit such facts or information.

10. Inspection and Entry

The permittee shall allow the Chief, or an authorized representative, upon the presentation of credentials and other documents as may be required by law, to:

- a) Enter upon the permittee's premises in which an effluent source or activity is located, or where records must be kept under the conditions of this permit;
- b) Have access to and copy at reasonable times, any records that must be kept under the conditions of this permit;
- c) Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
- d) Sample or monitor at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by the State Act, any substances or parameters at any location.

11. Permit Modification

This permit may be modified, suspended, or revoked in whole or in part during its term in accordance with the provisions of Chapter 22-11-12 of the Code of West Virginia.

12. Water Quality

The effluent or effluents covered by this permit are to be of such quality so as not to cause violation of applicable water quality standards adopted by the Environmental Quality Board.

13. Outlet Markers

A permanent marker at the establishment shall be posted in accordance with Title 47, Series 11, Section 9 of the West Virginia Legislative Rules.

14. Liabilities

a) Any person who violates a permit condition implementing sections 301, 302, 306, 307, 308, 318, or 405 of the Clean Water Act is subject to a civil penalty not to exceed \$10,000 per day of such violation. Any person who willfully or negligently violates permit conditions implementing sections 301, 302, 306, 307, or 308 of the Clean Water Act is subject to a fine of not less than \$2,500 nor more than \$25,000 per day of violation, or by imprisonment for not more than 1 year, or both.

b) Any person who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than 6 months per violation, or by both.

c) Any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or noncompliance shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than 6 months per violation, or by both.

d) Nothing in I.14 a), b), and c) shall be construed to limit or prohibit any other authority the Chief may have under the State Water Pollution Control Act, Chapter 22, Article 11.

DRAFT

I. OPERATION AND MAINTENANCE:

1. Proper Operation and Maintenance

The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls, and appropriate quality assurance procedures. Unless otherwise required by Federal or State law, this provision requires the operation of back-up auxiliary facilities or similar systems which are installed by the permittee only when the operation is necessary to achieve compliance with the conditions of the permit. For domestic waste treatment facilities, waste treatment operators as classified by the WV Bureau of Public Health Laws, W. Va. Code Chapter 16-1, will be required except that in circumstances where the domestic waste treatment facility is receiving any type of industrial waste, the Chief may require a more highly skilled operator.

2. Need to Halt or Reduce Activity Not a Defense

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit.

3. Bypass

a) Definitions

(1) "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility; and
(2) "Severe property damage" means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.

b) Bypass not exceeding limitations. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provision of II.3.c) and II.3.d) of this permit.

c) (1) If the permittee knows in advance of the need for a bypass, it shall submit prior notice, if possible at least ten (10) days before the date of the bypass;

(2) If the permittee does not know in advance of the need for bypass, notice shall be submitted as required in IV.2.b) of this permit.

d) Prohibition of bypass

(1) Bypass is permitted only under the following conditions, and the Chief may take enforcement action against a permittee for a bypass, unless;

(A) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;

(B) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate backup equipment should have been installed in the exercise of reasonable engineering judgement to prevent a bypass which occurred during normal periods of equipment downtime or preventative maintenance; and

(C) The permittee submitted notices as required under II.3.c) of this permit.

(2) The Chief may approve an anticipated bypass, after considering its adverse effects, if the Chief determines that it will meet the three conditions listed in II.3.d.(1) of this permit.

4. Upset

a) Definition. "Upset" means an exceptional incident in which there is unintentional and temporary noncompliance with technology-based permit effluent limitations because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventative maintenance, or careless or improper operation.

b) Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with such technology-based permit effluent limitation if the requirements of II.4.c) are met. No determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review.

c) Conditions necessary for a demonstration of upset. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:

(1) An upset occurred and that the permittee can identify the cause(s) of the upset;

(2) The permitted facility was at the time being properly operated;

(3) The permittee submitted notice of the upset as required in IV.2.b) of this permit.

(4) The permittee complied with any remedial measures required under I.3. of this permit.

d) Burden of proof. In any enforcement proceeding the permittee seeking to establish the occurrence of an upset has the burden of proof.

5. Removed Substances

Where removed substances are not otherwise covered by the terms and conditions of this permit or other existing permit by the Chief, any solids, sludges, filter backwash or other pollutants (removed in the course of treatment or control of wastewaters) and which are intended for disposal within the State, shall be disposed of only in a manner and at a site subject to the approval by the Chief. If such substances are intended for disposal outside the State or for reuse, i.e., as a material used for making another product, which in turn has another use, the permittee shall notify the Chief in writing of the proposed disposal or use of such substances, the identity of the prospective disposer or users, and the intended place of disposal or use, as appropriate.

DRAFT

III. MONITORING AND REPORTING

1. Representative Sampling

Samples and measurements taken for the purpose of monitoring shall be representative of the monitored activity.

2. Reporting

a) Permittee shall submit, according to the enclosed format, a Discharge Monitoring Report (DMR) indicating in terms of concentration, and/or quantities, the values of the constituents listed in Part A analytically determined to be in the plant effluent(s). DMR submissions shall be made in accordance with the terms contained in Section C of this permit.

b) Enter reported average and maximum values under "Quantity" and "Concentration" in the units specified for each parameter, as appropriate.

c) Specify the number of analyzed samples that exceed the allowable permit conditions in the columns labeled "N.E." (i.e., number exceeding).

d) Specify frequency of analysis for each parameter as number of analyses/specified period (e.g., 3/month is equivalent to 3 analyses performed every calendar month). If continuous, enter "Cont.". The frequency listed on format is the minimum required.

3. Test Procedures

Samples shall be taken, preserved and analyzed in accordance with the latest edition of 40 CFR Part 136, unless other test procedures have been specified elsewhere in this permit.

4. Recording of Results

For each measurement or sample taken pursuant to the permit, the permittee shall record the following information.

a) The date, exact place, and time of sampling or measurement;

b) The date(s) analyses were performed;

c) The individual(s) who performed the sampling or measurement;

d) The individual(s) who performed the analyses; if a commercial laboratory is used, the name and address of the laboratory;

e) The analytical techniques or methods used, and

f) The results of such analyses. Information not required by the DMR form is not to be submitted to this agency, but is to be retained as required in III.6.

5. Additional Monitoring by Permittee

If the permittee monitors any pollutant at any monitoring point specified in this permit more frequently than required by this permit, using approved test procedures or others as specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the Discharge Monitoring Report Form. Such increased frequency shall also be indicated. Calculations for all limitations which require averaging of measurements shall utilize an arithmetic mean unless otherwise specified in the permit.

6. Records Retention

The permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for the permit, for a period of at least three (3) years from the date of the sample, measurement, report or application. This period may be extended by request of the Chief at any time.

7. Definitions

a) "Daily discharge" means the discharge of a pollutant measured during a calendar day or within any specified period that reasonably represents the calendar day for purposes of sampling. For pollutants with limitations expressed in units of mass, the daily discharge is calculated as the total mass of the pollutant discharged over the day. For pollutants with limitations expressed in other units of measurement, the daily discharge is calculated as the average measurement of the pollutant over the day.

b) "Average monthly discharge limitation" means the highest allowable average of daily discharges over a calendar month, calculated as the sum of all daily discharges measured during a calendar month divided by the number of daily discharges measured during that month.

c) "Maximum daily discharge limitation" means the highest allowable daily discharge.

d) "Composite Sample" is a combination of individual samples obtained at regular intervals over a time period. Either the volume of each individual sample is proportional to discharge flow rates or the sampling interval (for constant volume samples) is proportional to the flow rates over the time period used to produce the composite. The maximum time period between individual samples shall be two hours.

e) "Grab Sample" is an individual sample collected in less than 15 minutes.

f) "is" = immersion stabilization - a calibrated device is immersed in the effluent stream until the reading is stabilized.

g) The "daily average temperature" means the arithmetic average of temperature measurements made on an hourly basis, or the mean value plot of the record of a continuous automated temperature recording instrument, either during a calendar month, or during the operating month if flows are of shorter duration.

h) The "daily maximum temperature" means the highest arithmetic average of the temperatures observed for any two (2) consecutive hours during a 24 hour day, or during the operating day if flows are of shorter duration.

i) The "daily average fecal coliform" bacteria is the geometric average of all samples collected during the month.

j) "Measured Flow" means any method of liquid volume measurement, the accuracy of which has been previously demonstrated in engineering practice, or which a relationship to absolute volume has been obtained.

k) "Estimate" means to be based on a technical evaluation of the sources contributing to the discharge including, but not limited to pump capabilities, water meters and batch discharge volumes.

l) "Non-contact cooling water" means the water that is contained in a leak-free system, i.e., no contact with any gas, liquid, or solid other than the container for transport; the water shall have no net poundage addition of any pollutant over intake water levels, exclusive of approved anti-fouling agents.

DRAFT

IV. OTHER REPORTING

1. Reporting Spills and Accidental Discharges

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities or penalties established pursuant to Title 47, Series 11, Section 2 of the West Virginia Legislative Rules promulgated pursuant to Chapter 22, Article 11.

Attached is a copy of the West Virginia Spill Alert System for use in complying with Title 47, Series 11, Section 2 of the Legislative rules as they pertain to the reporting of spills and accidental discharges.

2. Immediate Reporting

- a) The permittee shall report any noncompliance which may endanger health or the environment immediately after becoming aware of the circumstances by using the Agency's designated spill alert telephone number. A written submission shall be provided within five (5) days of the time the permittee becomes aware of the circumstances. The written submission shall contain a description of the noncompliance and its cause; the period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.
- b) The following shall also be reported immediately:
 - (1) Any unanticipated bypass which exceeds any effluent limitation in the permit;
 - (2) Any upset which exceeds any effluent limitation in the permit; and
 - (3) Violation of a maximum daily discharge limitation for any of the pollutants listed by the Chief in the permit to be reported immediately. This list shall include any toxic pollutant or hazardous substance, or any pollutant specifically identified as the method to control a toxic pollutant or hazardous substance.
- c) The Chief may waive the written report on a case-by-case basis if the oral report has been received in accordance with the above.
- d) Compliance with the requirements of IV.2 of this section shall not relieve a person of compliance with Title 47, Series 11, Section 2.

3. Reporting Requirements

- a) Planned changes. The permittee shall give notice to the Chief of any planned physical alterations or additions to the permitted facility which may affect the nature or quantity of the discharge. Notice is required when:
 - (1) The alteration or addition to a permitted facility may meet one of the criteria for determining whether a facility is a new source in Section 13.7.b of Series 10, Title 47; or
 - (2) The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants which are subject neither to effluent limitations in the permit, nor to notification requirements under IV.2 of this section.
- b) Anticipated noncompliance. The permittee shall give advance notice to the Chief of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
- c) In addition to the above reporting requirements, all existing manufacturing, commercial, and silvicultural discharges must notify the Chief in writing as soon as they know or have reason to believe:
 - (1) That any activity has occurred or will occur which would result in the discharge, on a routine or frequent basis, or any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels":
 - (A) One hundred micrograms per liter (100 ug/l);
 - (B) Two hundred micrograms per liter (200 ug/l) for acrolein and acrylonitrile; five hundred micrograms per liter (500 ug/l) for 2,4-dinitro phenol; and for 2-methyl 4,6-dinitrophenol; and one milligram per liter (1 mg/l) for antimony;
 - (C) Five (5) times the maximum concentration value reported for that pollutant in the permit application in accordance with Section 4.4.b.9 of Series 10, Title 47.
 - (D) The level established by the Chief in accordance with Section 6.3.g of Series 10, Title 47;
 - (2) That any activity has occurred or will occur which would result in any discharge (on a non-routine or infrequent basis) of a toxic which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels":
 - (A) Five hundred micrograms per liter (500 ug/l);
 - (B) One milligram per liter (1 mg/l) for antimony;
 - (C) Ten (10) times the maximum concentration value reported for that pollutant in the permit application in accordance with Section 4.4.b.7 of Series 10, Title 47;
 - (D) The level established by the Chief in accordance with Section 6.3.g of Series 10, Title 47.
 - (3) That they have begun or expect to begin to use or manufacture as an intermediate or final product or by-product of any toxic pollutant which was not reported in the permit application under Section 4.4.b.9 of Series 10, Title 47 and which will result in the discharge on a routine or frequent basis of that toxic pollutant at levels which exceed five times the detection limit for that pollutant under approved analytical procedure.
 - (4) That they have begun or expect to begin to use or manufacture as an intermediate or final product or by-product of any toxic pollutant which was not reported in the permit application under Section 4.4.b.9 of Series 10, Title 47 and which will result in the discharge on a non-routine or infrequent basis of that toxic pollutant at levels which exceed ten times the detection limit for that pollutant under approved analytical procedure.

4. Other Noncompliance

The permittee shall report all instances of noncompliance not reported under the above paragraphs at the time monitoring reports are submitted. The reports shall contain the information listed in IV.2.a). Should other applicable noncompliance reporting be required, these terms and conditions will be found in Section C of this permit.

DRAFT

Appendix D

Sediment and Erosion Control BMP manuals:

1. Erosion and Sediment Control BMP manual – WV DEP
2. Maryland Soil Erosion and Sediment Control BMP manual;
3. Virginia Erosion and Sediment Control Handbook;
4. USEPA has a listing of available stormwater manuals on its website.
5. West Virginia Department of Transportation, Division of Highways, Erosion and Sediment Control Manual, March 1, 2003.

DRAFT